

HH900 RFID Mobile Tracking



SPECS

TECHNICAL SPECIFICATIONS

- Dual-Band 900/ 1800 MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
- Class 4 (2 W @900 MHz)
- Class 1 (1 W @ 1800MHz)
- Low power consumption:
- Operation temperature: -40°C to +85 °C
- GPRS class 10•
- RoHS
- CE

- 32b uC
- 4000 Data Storage
- EM Marin RFID Reader
- GPRS Communication
 - 3x4 Keypad
 - 2 x 16 Character LCD
- Slot For Battery Connection
 - SMS Communication
 - GPS Module (Optional)
- Temperature And Humidity Measurement (Optional)
 - SIM Card Holder
 - Internal GSM Antenna
- Designed to Response to Mounted And Mobile Applications
 - Remote FW Updating
 - GSM Cell ID Notification
- Vehicle Tracker System (HH900 With GPS)
 - Emergency Status Info
 - Location Info Periodically (HH900 with GPS module)
 - Remote APN, IP and Port Config.
 - 10°C to +55°C
 - Dimensions: 105 x 205 x 41 mm
 - Weight: <200 gr



BIOS Limited Şirketi

M.Kemal Blv. Aktan Sok. 2048 Mimarsinan B.Çekmece İstanbul 34535-TR
Pbx. +90 212 8643311 Fax. +90 212 8643313 info@bios.com.tr www.bios.com.tr